

TRADE PACK

ULTRA550
5 WATT
UHF CB RADIOS



3 YEAR
WARRANTY*

 **oricom**[®]
100% AUSSIE OWNED

ULTRA550 TRADE PACK 5 WATT UHF CB RADIO

WITH HEAVY DUTY CASE



PACK INCLUDES:

- 2 x ULTRA550 UHF CB Radios
- 2 x Speaker mics
- 2 x Charging cradles
- 2 x AC adaptors
- 2 x 12v adaptors
- 2 x Belt clips
- 2 x Lithium-ion batteries
- 1 x Heavy duty waterproof case

RADIO FEATURES:

- Water and dust proof IP67
- Compact radio with large backlit LCD display
- Switchable RF power (high: 5 watt, low: 1 watt)
- 3 Programmable instant channel buttons
- 80 channels[†]
- Fast charge technology supplied with 240v and 12v adaptors
- Open/instant/priority scan
- Die-cast metal chassis
- Duplex (range extender)
- Signal monitoring
- Triple watch
- Audio scrambler
- Key lock function
- Squelch tail on/off
- 38 CTCSS and 104 DCS codes
- High-capacity Lithium-ion battery pack (2600mAh) with up to 30 hours operating time[^]
- Rotary volume control
- 2.5mm jack socket with locking screw for optional accessories
- Designed, engineered and produced in Korea

TECHNICAL SPECIFICATION

GENERAL

Compliance	AS/NZS 4365:2011 and NZS2772.1
Frequency Range TX/RX	476.425 - 477.4125 MHz
Number of Channels	80 UHF CB (75 Usable) [†]
Channel Spacing TX/RX	12.5KHz
Channel Spacing RX	12.5KHz
Operating modes	Simplex, Duplex
Scanning Speed	150msec/per channel
Antenna Impedance	50 Ohm
Battery Capacity	7.4V/2600mAh Li-ion Battery. Operating time up to 20hrs on High TX power, 30hrs on Low TX power with antenna.
Frequency Stability	+/- 2.5ppm

Transmitter

RF Output Power	5 Watts max.
Modulation	FM
Maximum Deviation	+/- 2.5KHz
Spurious Emissions	Less than -30dBm
Tx Frequency Response	+1 to -3dB of 6dB/octave from 300Hz to 3000Hz
Audio Signal to Noise Ratio	more than 35dB

Receiver

Circuit Type	Direct conversion by Single DSP chip
Intermediate Frequencies	IF = 137KHz
Sensitivity	Less than -122dBm at 12dB SINAD
Selectivity	more than 70dB
Intermodulation Immunity	more than 70dB
Spurious Response Immunity	more than 60dB
Audio Signal to Noise Ratio	More than 50dB
Receive Frequency Response	+1 to -3dB of 6dB/octave from 300Hz to 3000Hz
Conducted Spurious Emissions	Less than -57dBm at 9KHz



oricom.com.au

Oricom® is the registered trademark of Oricom International Pty Ltd.

*3 year warranty excludes battery, accessories and hard case.

[^]30 hours operating time using low power, 20 hours using high power with antenna. Duty cycle: 5% transmit, 5% receive and 90% standby.

 **oricom**[®]
100% AUSSIE OWNED